

	External dimensions			Internal dimensions			Door aperture		Weight			Characteristics		
	Length, mm	Width, mm	Height, mm	Length, mm	Width, mm	Height, mm	Width, mm	Height, mm	Maximum gross weight, kg	Tare weight, kg	Maximum load capacity, kg	Capacity, m³	Stacking, tiers	Amount of holded europallets (1200x800 mm), pcs.
20'DV	6058	2438	2591	5905	2350	2381	2336	2291	24000 - 30480	2145 - 2370	21630 - 28335	33 - 33,2	86400,9	11
20'HC	6058	2438	2896	5905	2350	2693	2340	2597	30480	2340	28140	37,5	86400,9	11
40'DV	12192	2438	2591	12039	2350	2372	2336	2291	28800 - 30480	3640 - 4000	24800 - 26840	67,3 - 67,8	86400,7	25
40'HC	12192	2438	2896	12039	2350	2693	2340	2597	30480 - 32500	3740 - 4200	26280 - 28650	75,6 - 76,5	86400,7	25
40'PW	13553	2426	2694	12100	2426	2684	2360	2585		4150		79,1		30
45'HC	13716	2438	2896	13556	2352	2698	2343	2585	30400	4590	25600	86,1		
45'HCPW	13716	2500	2750	13513	2444	2549	2416	2439	34000	4180	29820	85,1	86400,5	33