

	External dimensions			Internal dimensions			Door aperture		Weight			Characteristics
	Length, mm	Width, mm	Height, mm	Length, mm	Width, mm	Height, mm	Width, mm	Height, mm	Maximum gross weight, kg	Tare weight, kg	Maximum load capacity, kg	Capacity, m ³
20'OT	6045	2438	2591	5893	2377	2388	2237	2286	24000	2400	21600	32,9
40'OT	12192	2438	2591	12050	2330	2350	2337	2286	30930	4300	26630	67,1
20'HT	6060	2438	2590	5890	2320	2354	2300	2350	24000	2400	21600	32,2
40'HT	12192	2438	2590	12050	2350	2354	2340	2350	30300	3800	26500	66,5
20'FR	6045	2438	2591	5893	2210	2213			34000	2740	31260	32,9
40'FR	12086	2224	2591	11826	2224	2350			30480	4200	26280	67,1
20'PF	6060	2438	2590	5650	2350	2230			31000	3000	28000	
40'PF	12192	2438	2590	12080	2430	2100			45000	5000	40000	
20'FT Bulk containers	6058	2438	2591	5934	2358	2340	2335	2292	24000	2450	21550	33
20'FT Ventilated Containers	6100	2502	2997	6002	2397	2703	5552	2664				
Open Side Container	6058	2438	2591	5898	2287	2299	6000	2299	24000	3200	20800	33 - 33,2